

General Purpose Perforated Worm-Gear Hose Clamps

Breeze Mini

A lightweight, streamlined clamp generally used in small diameter applications such as air & fuel lines. The streamlined configuration allows for installation in tight fitting or difficult to reach areas. This clamp creates high sealing pressure with only 10 to 15 in./lbs (1.1-1.7 Nm) of installation torque.

5/16" (7.9 mm) band

1/4" (6.4 mm) slotted hex head screw

Per SAE standard J1508 Type "M"



SAE Size	EFFECTIVE DIAMETER RANGE				PART NUMBERS			
	Min.		Max.		Plated Hex Screw	410 S. S. Hex Screw	300 S. S. Hex Screw	All 316 S. S.
	in.	mm	in.	mm				
4	7/32	5.6	5/8	16	3504	3604	3704	3804
6	7/16	11	25/32	20	3506	3606	3706	3806
8	1/2	13	29/32	23	3508	3608	3708	3808
10	9/16	14	1-1/16	27	3510	3610	3710	3810
12	11/16	17	1-1/4	32	3512	3612	3712	
16	15/16	24	1-1/2	38	3516	3616	3716	
20	1-3/16	30	1-3/4	44	3520	3620	3720	
24	1-7/16	37	2	51	3524	3624	3724	
28	1-11/16	43	2-1/4	57	3528	3628	3728	
32	1-15/16	49	2-1/2	64	3532	3632	3732	

